



Advanced Card Systems Ltd.
Card & Reader Technologies

ACR38U-I1

Smart Card Reader



Technical Specifications V1.11



Table of Contents

1.0.	Introduction	3
1.1.	Smart Card Reader.....	3
1.2.	Modern Design	3
1.3.	Ease of Integration.....	3
2.0.	Features	4
3.0.	Supported Card Types.....	5
3.1.	MCU Cards	5
3.2.	Memory-based Smart Cards.....	5
4.0.	Typical Applications	6
5.0.	Technical Specifications	7



1.0. Introduction

ACR38U-I1 is the latest addition to the ACR38 PC-linked Smart Card Reader Series. Combining secure smart card reader technology functionalities with a sleek and modern design, ACR38U-I1 is the perfect peripheral for your smart card applications.



1.1. Smart Card Reader

ACR38U-I1 supports ISO 7816 Class A, B and C smart cards and microprocessor cards with the T=0 and T=1 protocol. It also supports a wide variety of memory cards in the market, including the Department of Defense Common Access Card (CAC). This makes it perfect for a broad range of solutions, such as PIV Application, Physical and Logical Access Control, Digital Signature, and Online Banking.

1.2. Modern Design

The new sleek and stylish design of ACR38U-I1 makes it stand out from ordinary smart card readers. This trendy device houses the powerful ACR38 core, which has been proven to support highly demanding smart card applications. It also features a USB Full Speed interface and a smart card reader/writer speed of 344 Kbps. Highly durable, ACR38U-I1 can last for at least 100,000 card insertion cycles.

1.3. Ease of Integration

ACR38U-I1 is easy to install, use and integrate into a computer-based environment. It is PC/SC and CCID compliant, and its drivers are compatible with operating systems such as Windows®, Linux® and Mac OS®. In addition, ACR38U-I1 may now be used on mobile devices running the Android™ platform with versions 3.1 and above.

With its various features, the ACR38U-I1 is the perfect smart card reader for your smart card solution.



2.0. Features

- USB 2.0 Full Speed Interface
- Plug and Play – CCID support brings utmost mobility
- Smart Card Reader:
 - Supports ISO 7816 Class A, B and C (5 V, 3 V, 1.8 V) cards
 - Supports CAC (Common Access Card)
 - Supports J-LIS Card
 - Supports microprocessor cards with T=0 or T=1 protocol
 - Supports memory cards
 - Supports PPS (Protocol and Parameters Selection)
 - Features Short Circuit Protection
- Application Programming Interface:
 - Supports PC/SC
 - Supports CT-API (through wrapper on top of PC/SC)
- Supports Android™ 3.1 and later¹
- Compliant with the following standards:
 - EN60950/IEC 60950
 - ISO 7816
 - EMV™ Level 1 (Contact)
 - PC/SC
 - CCID
 - CE
 - FCC
 - UL
 - RoHS 2
 - REACH
 - FIPS 201 (USA)
 - TAA (USA)
 - J-LIS (Japan)
 - VCCI (Japan)
 - KC (Korea)
 - Microsoft® WHQL

¹ Uses an ACS-defined Android Library



3.0. Supported Card Types

3.1. MCU Cards

ACR38U-I1 operates with ISO 7816 MCU card following either the T=0 or T=1 protocol. It also works with CAC cards, ideal for US PIV and PKI applications.

3.2. Memory-based Smart Cards

ACR38U-I1 works with several memory-based smart cards such as:


- Cards following the I2C bus protocol (free memory cards) with maximum 128 bytes page with capability, including:
 - Atmel®: AT24C01/02/04/08/16/32/64/128/256/512/1024
 - SGS-Thomson: ST14C02C, ST14C04C
 - Gemplus: GFM1K, GFM2K, GFM4K, GFM8K
- Cards with secure memory IC with password and authentication, including:
 - Atmel®: AT88SC153 and AT88SC1608
- Cards with intelligent 1 KB EEPROM with write-protect function, including:
 - Infineon®: SLE4418, SLE4428, SLE5518 and SLE5528
- Cards with intelligent 256-byte EEPROM with write-protect function, including:
 - Infineon®: SLE4432, SLE4442, SLE5532 and SLE5542
- Cards with '104' type EEPROM non-reloadable token counter cards, including:
 - Infineon®: SLE4406, SLE4436, SLE5536 and SLE6636
- Cards with Intelligent 416-bit EEPROM with internal PIN check, including:
 - Infineon®: SLE4404
- Cards with Security Logic with Application Zone(s), including:
 - Atmel®: AT88SC101, AT88SC102 and AT88SC1003



4.0. Typical Applications

- e-Government
- e-Banking and e-Payment
- e-Healthcare
- Public Key Infrastructure
- Network Security
- Access Control
- Loyalty Program

5.0. Technical Specifications



Physical Characteristics

Dimensions 72.2 mm (L) × 69.0 mm (W) × 14.5 mm (H)
 Weight 65 g (± 5 g allowance for cable)
 Color White

USB Host Interface

Protocol USB CCID
 Type Four Lines: +5 V, GND, D+ and D-
 Connector Type Standard Type A
 Power Source From USB port
 Speed USB Full Speed (12 Mbps)
 Supply Voltage 5 V
 Cable length 1.5 m fixed cable

Contact Smart Card Interface

Number of Slots 1 Full-sized Card Slot
 Standard ISO 7816 Parts 1-3, Class A, B, C (5 V, 3 V, 1.8 V)
 Protocol T=0; T=1; Memory Card Support
 Supply Current Max. 50 mA
 Smart Card Read/Write Speed 9.6 Kbps - 344 Kbps
 Short Circuit Protection (+5) V/GND on all pins
 Clock Frequency 4.0 MHz
 Card Connector Type ICC Slot 1: Contact
 Card Insertion Cycles Min. 100,000

Built-in Peripheral

LED Green

Application Programming Interface

PC-linked Mode PC/SC
 CT-API (through wrapper on top of PC/SC)

Operating Conditions

Temperature 0 °C - 50 °C
 Humidity Max. 90% (non-condensing)
 MTBF 500,000 hrs




Certifications/Compliance

EN60950/IEC 60950, ISO 7816, USB Full Speed, EMV™ Level 1 (Contact), PC/SC, CCID, CE, FCC, UL, RoHS 2, REACH, FIPS 201 (USA), TAA (USA), J-LIS (Japan), VCCI (Japan), KC (Korea), Microsoft® WHQL

Device Driver Operating System Support

Windows® CE, Windows® ME, Windows® 98, Windows® 2000, Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10
Windows® Server 2003, Windows® Server 2008, Windows® Server 2008 R2, Windows® Server 2012, Windows® Server 2012 R2
Linux®, Mac OS®, Android™ 3.1 and later



Android is a trademark of Google Inc.
Atmel is registered trademark of Atmel Corporation or its subsidiaries, in the US and/or other countries.
EMV is a registered trademark or trademark of EMVCo LLC in the United States and other countries.
Infineon is a registered trademark of Infineon Technologies AG.
Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.
Mac OS is a trademark of Apple Inc., registered in the U.S. and other countries.
Microsoft, Windows and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries.